



Typical Chemical Characteristics

Product:

MX 2T “Fully Synthetic Anti-smoke Racing Oil”

Description:

EN

Fully synthetic racing oil mixable with fuel, proper for two stroke engines only. It is recommended for analogy less than 3%. It is absolutely ideal for racing use in exhausting conditions. It's unique formulation contains special additives for having anti-smoke properties.

EL

Αγωνιστικής χρήσης πλήρως συνθετικό λιπαντικό ειδικό για ανάμιξη με βενζίνη και για χρήση σε δίχρονους κινητήρες. Προσφέρει άψογο μίγμα με το καύσιμο σε αναλογία <3% και τέλεια λίπανση στον κινητήρα χωρίς να αφήνει κατάλοιπα καθώς βελτιώνει την καύση. Επίσης η μοναδική του σύνθεση περιέχει ειδικά πρόσθετα ώστε να μην δημιουργεί καπνό κατά την καύση του.

DE:

Vollständiges Sortiment an mit Treibstoff mischbaren Racing Ölen, geeignet nur für Zweitaktmotoren. Empfohlenes Mischverhältnis unter 3%. Die absolut ideale Lösung für Racing unter harten Bedingungen. Die einmalige Formel enthält spezielle Additive gegen Rauchentwicklung.

RU:

Полностью синтетическое масло для смешивания с топливом, предназначенное только для двухтактных двигателей. Рекомендуется смешивать в пропорции не более 3%. Идеально подходит для применения в жестких гоночных условиях. Уникальный состав содержит специальные присадки с противодымными свойствами.

Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



Typical Chemical Characteristics

Characteristics:

Property	Method	Unit	Result
Specific Gravity 15°C	ASTM D 1298	kg/L	0,88
Viscosity at 100°C	ASTM D 445	cSt	9,5 - 12,2
Viscosity at 40°C	ASTM D 445	cSt	75 - 85
Viscosity Index	-	-	> 120
Pour Point	ASTM D 97	°C	<-30
Flash Point	ASTM D 92	°C	≥ 110
Colour	-	-	Crystal red

Specifications:

API: TC
 JASO FB/FC
 ISO-L-EGD

Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.