



Typical Chemical Characteristics

Product:

SS 2T “Semi Synthetic”

Description:

EN:
Semi Synthetic lubricant from high quality first materials for use in two stroke engines only. It provides less smoke, high lubrication, no residues and combustion chamber's purity. The suggested analogy is 50:1 with fuel. It is also recommended for racing use.

EL:
Ημισυνθετικό λιπαντικό για δίχρονους κινητήρες ιδανικό ακόμη και για αγωνιστική χρήση. Έχει ειδική σύνθεση ώστε να μειώνει τους ρύπους και να ελαχιστοποιεί το φαινόμενο άσχημης οσμής.

DE:
Halbsynthetisches Schmiermittel aus hochqualitativen Materialien ausschließlich für Zweitaktmotoren. Es bietet geringere Rauchentwicklung, gute Schmierung und hält den Verbrennungsraum sauber und frei von Rückständen. Das empfohlene Mischverhältnis mit Treibstoff beträgt 50:1. Auch geeignet für Racing-Anwendungen.

RU:
Полусинтетическое масло, изготовленное из высококачественных материалов и предназначенное только для двухтактных двигателей. Обеспечивает пониженное дымовыделение, хорошие смазывающие свойства, отсутствие осадка и чистоту камеры сгорания. Предполагаемая пропорция смешивания с топливом – 50:1. Также рекомендуется для применения в гоночных агрегатах.

Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



Typical Chemical Characteristics

Characteristics:

Property	Method	Unit	Result
Specific Gravity 15°C	ASTM D 1298	kg/L	0,88
Viscosity at 100°C	ASTM D 445	cSt	7,5
ISO EGD 3h Detergency	Engine Test	-	≥ 125
ISO EGD 3h Varnish Index	Engine Test	-	≥ 95
Viscosity Index	-	-	> 95
TISI Detergency	Engine Test	-	≥ 48

Specifications:

API: TC
 JASO FC
 ISO-L-EGD/EGC

Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.