



TCC (Typical Chemical Characteristics)

AGRON UTTO SAE 85W & SAE 80W

Description:

EN:
Universal Transmission Tractor Oil (**U.T.T.O.**) especially formulated for new generation and for older generation, of agricultural and forestry machineries. This universal oil is for use in hydraulic, in transmission, in differential and in wet brakes systems.

EL:
Νέο ευρείας χρήσης λιπαντικό (**U.T.T.O.**) για νέας αλλά και παλαιότερης τεχνολογίας αγροτικών ή δασικών μηχανημάτων. Αυτό το λιπαντικό προτείνεται για χρήση στο υδραυλικό σύστημα, στο σύστημα μετάδοσης κίνησης, στο σύστημα διαφορικού αλλά και επίσης στο σύστημα υδραυλικής πέδησης.

DE:
Universelles Traktor-Getriebeöl (**U.T.T.O.**) speziell entwickelt für die neue Traktorgeneration, aber auch geeignet für Traktoren der älteren Generationen. Dieses universelle Öl eignet sich für Hydraulik- und Getriebesysteme, für Differentialbremssysteme und feuchte Bremssysteme. Der Gebrauch als Motoröl ist jedoch nicht empfohlen.

FR:
Huile "Universal Transmission Tractor Oil" (**U.T.T.O.**) spécialement formulée pour la nouvelle génération de tracteurs, mais également pour les générations plus âgées. Cette huile universelle est employée en systèmes hydrauliques, de transmission, différentiels et de freins mouillés. Mais son emploi comme huile moteur n'est pas recommandé.

RU:
Универсальное трансмиссионное масло «Universal Transmission Tractor Oil» (**U.T.T.O.**) предназначено специально для тракторов нового поколения, но может также использоваться и в более старых моделях. Это универсальное масло подходит для гидравлических и трансмиссионных систем, дифференциалов и тормозных систем мокрого типа. Не рекомендуется для использования в качестве моторного масла.

BG:
Универсално трансмиссионно масло за трактори (**U.T.T.O.**) специално формулирано за трактори от ново и от по-старо поколение. Предназначено е за трансмисии, диференциали, както и за спирачната система. Не се препоръчва за употреба като моторно масло.

Characteristics:

Property	Method	Unit	10W-30/80W/ISO 68	20W-30/85W/ISO 100
Specific Gravity 15°C	ASTM D 1298	kg/L	0,888	0,890
Viscosity at 100°C	ASTM D 445	cSt	9,3 - 11,0	11,0 - 12,5
Viscosity Index	-	-	>115	>110
Pour Point	ASTM D 97	°C	<25	<20
Flash Point	ASTM D 92	°C	>210	>210
Total Base Number	ASTM D 2896	mgKOH/g	>10,5	>10,5
Color	-	-	Crystal gold	Crystal gold
Cold Cranking Simulator	ASTM D 5293	mPa-s	<3500 @ -20°C	<4500 @ -10°C

RS Laboratory: 27.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



TCC (Typical Chemical Characteristics)

AGRON UTTO SAE 85W & SAE 80W

Specifications:

SAE 85W / SAE 20W-30 / ISO 100:

API: GL-4, John Deere J20C / J20D, Allison C-4,
Ford M2C 86B / 86C / 134D, Part II Caterpillar CAT TO-2,
Massey Ferguson CMS M1135 / M1143 / M1145,
J.I. Case/Case int. MS-1204 / 1206 / 1207 / 1209,
CNH MAT 3525 / 3526, Sperry Vickers / EATON: M2950S / I-286-S,
Sauer Sunstrand / Danfoss: Hydrostatic Trans Fluid (Suitable for WET BRAKES)

SAE 80W / SAE 10W-30 / ISO 68:

API: GL-4, John Deere J20C / J20D, Allison C-4,
Ford M2C 86B / 86C / 134D, Part II Caterpillar CAT TO-2,
Massey Ferguson CMS M1135 / M1143 / M1145 ,
J.I. Case/Case int. MS-1204 / 1206 / 1207 / 1209,
CNH MAT 3525 / 3526, Sperry Vickers / EATON: M2950S / I-286-S,
Sauer Sunstrand / Danfoss: Hydrostatic Trans Fluid (Suitable for WET BRAKES)

Application:

AGRON UTTO SAE 85W:

18L (plastic)	204L
646085187	646085247

AGRON UTTO SAE 80W:

18L (plastic)	204L
646080187	646080247

Package:

1x18L Plastic Pail / 1x204L Drum



RS Laboratory: 27.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.