



## TCC (Typical Chemical Characteristics)

### AUTOMATIC-2T Mineral Oil

---

#### Description:

EN:

Smokeless oil mixable with gasoline for all two strokes engines. The contained aromatic additives does not cause bad smell through the exhaust.

EL:

Αρωματισμένο λιπαντικό ιδανικό για όλους τους δίχρονους κινητήρες με χρήση σε εντός ή εκτός πόλης. Προσφέρει μέγιστη λίπανση, ελαχιστοποίηση καπνού και εύκολη ανάμιξη με την βενζίνη.

DE:

Rauchfreies 2T Öl mit aromatischen Additiven gegen unangenehmen Abgasgeruch. Absolut geeignet für alle Zweitaktmotoren.

FR:

Huile 2T sans fumée contenant des additifs aromatiques pour éliminer l'odeur désagréable du gaz d'échappement. Convient parfaitement à tous les moteurs à deux temps.

RU:

Бездымное масло для двухтактных двигателей с ароматизирующими добавками, устраняющими неприятный запах выхлопных газов. Идеально подходит для всех двухтактных двигателей.

---

RS Laboratory: 16.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: [rs200motoroil.com](http://rs200motoroil.com)



**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



## TCC (Typical Chemical Characteristics)

### AUTOMATIC-2T Mineral Oil

#### Characteristics:

Property	Method	Unit	Result
Specific Gravity 15°C	D 1298	kg/L	0,87
Viscosity at 100°C	D 445	cSt	8,5 - 9,5
TC Sequence I (detergency)			
Avg. Piston Varnish	-	-	5,6
2 <sup>nd</sup> ring stick	-	-	8,8
TC Sequence II (Lubricity)	-	-	5,11
Smoke Index	-	-	>85
Blocking Index	-	-	>90
Torque Index	-	-	>98
Lubricity Index	-	-	>95

#### Specifications:

##### **AUTOMATIC-2T:**

API: TC,  
JASO FC / FB  
& ISO-L-EGC

1L	60L
<b>043021017</b>	<b>043021607</b>

#### Package:

12x1L Carton / 1x60L Mini-Drum



RS Laboratory: 16.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: [rs200motoroil.com](http://rs200motoroil.com)



**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.