



## TCC (Typical Chemical Characteristics)

### SUPER Hydraulic ISO 32 / 46 / 68

#### Description:

EN:  
Super enforced mineral hydraulic fluid suitable for most exhaustive conditions. Also shows great endurance against oxidization, corrosion and wear.

EL:  
Υπέρ ενισχυμένο πρωτογενές υδραυλικό υγρό για να ανταπεξέρχεται στις πιο δύσκολες συνθήκες. Περιέχει ειδικά πρόσθετα για να αντέχει στις υψηλές πιέσεις και να προστατεύει τα εσωτερικά μέρη του συστήματος.

DE:  
Hochverstärkte mineralische Hydraulikflüssigkeit, geeignet für die anspruchsvollsten Bedingungen. Zudem äußerst oxidations-, korrosions- und verschleißfest.

FR:  
Super hydraulique huile adapté pour la plupart des conditions exhaustives. Elle montre aussi une grande endurance contre l'oxydation, la corrosion et l'usure.

RU:  
Чрезвычайно эффективная минеральная гидравлическая жидкость, подходящая для использования в самых суровых условиях. Также демонстрирует хорошую стойкость к окислению, коррозии и износу.

BG:  
Супер подсилена минерална хидравлична течност, подходяща за най-екстремни условия. Продължителна защита от оксидация, корозия и износване.

#### Characteristics:

Property	Method	Unit	ISO 32	ISO 46	ISO 68
Code	-	-	RHSUH032	RHSUH046	RHSUH068
Specific Gravity 15°C	ASTM D 1298	kg/L	0,87	0,875	0,88
Viscosity at 40°C	ASTM D 445	cSt	28,8 - 35,2	41,4 - 50,6	61,2 - 74,8
Viscosity Index	-	-	>98	>98	>98
Pour Point	ASTM D 97	°C	<10	<10	<10
Flash Point	ASTM D 92	°C	>200	>200	>200
Color	-	-	Crystal gold	Crystal gold	Crystal gold

RS Laboratory: 10.02.2023

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: [rs200motoroil.com](http://rs200motoroil.com)



**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



## TCC (Typical Chemical Characteristics)

### SUPER Hydraulic ISO 32 / 46 / 68

#### Specifications:

##### ISO 68:

Part II HLP  
DIN 51524

18L	204L
<b>156068187</b>	<b>156068247</b>

##### ISO 46:

Part II HLP  
DIN 51524

18L	204L
<b>156046187</b>	<b>156046247</b>

##### ISO 32:

Part II HLP  
DIN 51524

18L	204L
<b>1456032187</b>	<b>156032247</b>

#### Package:

1x18L Pail / 1x204L Drum



RS Laboratory: 10.02.2023

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece [EU] - website: [rs200motoroil.com](http://rs200motoroil.com)



**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.