



TCC (Typical Chemical Characteristics)

ATT ISO 32, 46, 68 & 100

Description:

EN:

High quality lubricant for extended usage. Suitable for palidromic air compressors. It provides excellent performance in all uses and magnificent high endurance. Compatible with all waterproof parts.

EL:

Άριστης ποιότητας λιπαντικό με μεγάλη διάρκεια ζωής για παλινδρομικούς αεροσυμπιεστές. Είναι συμβατό με όλα τα αλεξυδάτα μέρη των συστημάτων και παρουσιάζει εφάμιλλη απόδοση με αυτή των συνθετικών.

DE:

Hochqualitäts- Schmiermittel für den Dauergebrauch. Geeignet für alle Schwingkompressoren. Bietet hervorragende Leistung in jeder Anwendung und überraschend hohe Belastbarkeit. Kompatibel mit allen wasserdichten Teilen.

FR:

Lubrifiant de haute qualité pour un usage prolongé. Convient pour les compresseurs d'air palindromiques. Il offre d'excellentes performances dans tous les usages et une grande endurance magnifique. Compatible avec toute pièce imperméable.

RU:

Высококачественное компрессорное масло с длительным сроком службы. Подходит для палидромных воздушных компрессоров. Обеспечивает отличную эффективность при любых условиях эксплуатации и великолепную выносливость. Совместимо со всеми водонепроницаемыми деталями.

BG:

Висококачествено масло, подходящо при продължителна експлоатация. Подходящо за въздушни компресори. Осигурява отлични показатели при всякаква употреба за дълъг период от време. Съвместимо с всички водоустойчиви части.

SR:

Visokokvalitetno mazivo za višecerasovnu upotrebu u radu. Pogodno za kompresore. Posедуje izuzetne performanse u svim uslovima i fantasticnu otpornost. Kompatibilno sa svim vodootpornim delovima.

RS Laboratory: 28.03.18 - Chemical Engineer: Periklis Kateris

© copyright RS200 motor oil - Papantoniou A.B.E.E. - Industrial Zone of Lakkoma - Halkidiki - Greece (Hellas) - GR-63080 - POB 53 - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



TCC (Typical Chemical Characteristics)

ATT ISO 32, 46, 68 & 100

Characteristics:

Property	Method	Unit	VG-32	VG-46	VG-68	VG-100
Code	-	-	RIATT032	RIATT046	RIATT068	RIATT100
Specific Gravity 15°C	ASTM D 1298	kg/L	0,87	0,875	0,88	0,885
Viscosity at 40°C	ASTM D 445	cSt	28,8 - 35,2	41,4 - 50,6	61,2 - 74,8	90 - 110
Viscosity Index	-	-	>115	>115	>115	>115
Pour Point	ASTM D 97	°C	<25	<25	<25	<25
Flash Point	ASTM D 92	°C	>205	>210	>210	>215
Color	-	-	Crystal gold	Crystal gold	Crystal gold	Crystal gold

Specifications:

DIN 51506
ISO/DP 6521 (DAA, DAB, DAH, DAG)

RS Laboratory: 28.03.18 - Chemical Engineer: Periklis Kateris

© copyright RS200 motor oil - Papantoniou A.B.E.E. - Industrial Zone of Lakkoma - Halkidiki - Greece (Hellas) - GR-63080 - POB 53 - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.