



Description:

EN:
Fully synthetic fluid in low viscosity for new 6-speed automatic transmission systems. It is specially formulated with superb additive technology for excellent mechanical operation. It covers a wide range of automatic transmission systems such as **Acura, Allison, Audi, BMW, Chrysler, Daimler, Dodge, Ford, GM, GMC, Honda, Hyundai, Isuzu, Jaguar, Jeep, Land Rover, Lincoln, Mercedes, Mercury, Mini, Mitsubishi, Nissan, Opel, Saturn, Toyota, Volkswagen, Volvo** etc.

EL:
Πλήρες συνθετικό λεπτόρευστο υγρό για νέα 6-τάχυτητα συστήματα αυτόματης μετάδοσης κίνησης. Είναι ειδικά κατασκευασμένο με εξαιρετης τεχνολογίας πρόσθετα για τέλεια μηχανική λειτουργία. Καλύπτει μια ευρεία σειρά από συστήματα αυτόματης μετάδοσης κίνησης όπως: **Acura, Allison, Audi, BMW, Chrysler, Daimler, Dodge, Ford, GM, GMC, Honda, Hyundai, Isuzu, Jaguar, Jeep, Land Rover, Lincoln, Mercedes, Mercury, Mini, Mitsubishi, Nissan, Opel, Saturn, Toyota, Volkswagen, Volvo** etc.

DE:
Vollsynthetische Flüssigkeit mit geringer Viskosität für die neuen 6-Gang- Automatik-Getriebesysteme. Spezielle Formel mit ausgezeichneter Additiv-Technologie für hervorragenden mechanischen Betrieb. Geeignet für zahlreiche Automatik-Getriebesysteme, wie etwa **von Acura, Allison, Audi, BMW, Chrysler, Daimler, Dodge, Ford, GM, GMC, Honda, Hyundai, Isuzu, Jaguar, Jeep, Land Rover, Lincoln, Mercedes, Mercury, Mini, Mitsubishi, Nissan, Opel, Saturn, Toyota, Volkswagen, Volvo** usw.

FR:
Fluide entièrement synthétique à faible viscosité pour les nouveaux systèmes à 6 vitesses de transmission automatique. Spécialement formulé avec une technologie d'additif superbe pour un excellent fonctionnement mécanique. Il couvre un large éventail de systèmes de transmission automatiques dont **Acura, Allison, Audi, BMW, Chrysler, Daimler, Dodge, Ford, GM, GMC, Honda, Hyundai, Isuzu, Jaguar, Jeep, Land Rover, Lincoln, Mercedes, Mercury, Mini, Mitsubishi, Nissan, Opel, Saturn, Toyota, Volkswagen, Volvo** etc.

RU:
Полностью синтетическая жидкость с низкой вязкостью для новых 6-ступенчатых автоматических коробок переключения передач. Специальный технологический процесс с применением современных присадок для превосходной механической работы. Охватывает широкий спектр автоматических систем переключения передач, таких как **Acura, Allison, Audi, BMW, Chrysler, Daimler, Dodge, Ford, GM, GMC, Honda, Hyundai, Isuzu, Jaguar, Jeep, Land Rover, Lincoln, Mercedes, Mercury, Mini, Mitsubishi, Nissan, Opel, Saturn, Toyota, Volkswagen, Volvo** и т.д.

PT :
Óleo totalmente sintético de baixa viscosidade para os novos sistemas de transmissão automática de 6 velocidades. É especialmente formulado com uma superior tecnologia de aditivos para excelente operação mecânica. Abrange uma ampla gama marcas de automóveis como, **Acura, Allison, Audi, BMW, Chrysler, Daimler, Dodge, Ford, GM, GMC, Honda, Hyundai, Isuzu, Jaguar, Jeep, Land Rover, Lincoln, Mercedes, Mercury, Mini, Mitsubishi, Nissan, Opel, Saturn, Toyota, Volkswagen, Volvo** etc.

RS Laboratory: 28.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



TCC (Typical Chemical Characteristics)

ATF LV

Characteristics:

Property	Method	Unit	Range
Code	-	-	RTATFLVO
Specific Gravity 20°C	ASTM D 1298	kg/L	0,85 - 0,87
Viscosity at 100°C	ASTM D 445	cSt	5,0 - 6,5
Viscosity Index	-	-	>130
Pour Point	ASTM D 97	°C	<50
Flash Point	ASTM D 92	°C	>205
Color	-	-	Red or Amber
Brookfield Viscosity @ -40°C	ASTM D 2893	cP	<15.000
Good Seal Compatibility	-	-	Pass
Good Oxidation resistance	-	-	Pass

Specifications:

JASO 1A LV, Ford Mercon-LV, GM D-VI / D-IIIH, MB 236.12 / 236.14 / 236.15 / 236.41, Audi & VW G 052 540 / G 055 005/ G 055 162, Bentley PY112995PA, BMW 83 22 0 142 516, Volvo 6 Speed (MY 2011-2013 P/N 31256774 / 31256675), Jaguar Fluid 8432, Land Rover TYK500050, Maserati 231603, Saab 93 165 147, Nissan Matic D / J / S / W, Honda ATF DW1 / Z1, Toyota T / T-II / T-III / T-IV / T-WS (JWS 3324), Hyundai & KIA SP-III / SP-IV / SPH-IV / SP-IV RR / SP-IV M / Hyundai NWS-9638, Subaru F6, Daihatsu AMMIX D-III Multi / D3-SP, Suzuki AT 5D06 / 2384K / JWS 3314 / JWS3317, Mazda M-III / M-V / JWS 3314 / JWS 3317, Mitsubishi SP-II / -IIM / III / Diaqueen PA / J3 / SP-IV & AISIN Warner JWS 3309 / 3324 / ATF-OWS / AW-1, ATF 134 / 3353 / ETL-7045 E / K17 / LA 2634 / N402, DSIH 6p805 (Geely, Ssangyong Mahindra 6 sp) & ZF S671 090 255 (6 Speed)

1L	60L
143770017	143770607

Package:

12x1L Carton / 1x60L Mini-Drum



RS Laboratory: 28.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.