



TCC (Typical Chemical Characteristics)

RR 4T SAE 0W-40 / 5W-40 / 10W-60 / 10W-50

Description:

EN

It belongs to the latest technology formula of fully synthetic lubricant absolutely suitable for race conditions. Includes special additives for offering stability and excellent behaviour under hard drive conditions gadding in the same time longer oil change spaces.

EL

Αναβαθμισμένο και πλήρες συνθετικό πολύτυπο λιπαντικό για της νέας γενιάς τετράχρονους κινητήρες μοτοό. Είναι κατάλληλο για χρήση σε αγωνιστικές μηχανές εκτός ή εντός δρόμου πολύστροφες ή μη αλλά και απολύτως ιδανικό για κινητήρες καθημερινής χρήσης. Χαρακτηριστικά του είναι η τέλεια λίπανση και η σταθερή λειτουργία ακόμα και όταν υπάρχει μηχανική καταπόνηση αλλά και τα μεγάλα διαστήματα αλλαγών λαδιών.

DE:

Vollsynthetische Schmiermittel-Formel nach der neuesten Technologie, optimal für Racing- Bedingungen. Enthält spezielle Additive für Stabilität und hervorragendes Fahrverhalten unter harten Bedingungen, und dies bei längeren Ölwechselintervallen.

FR:

Il appartient à la dernière formule de technologie de lubrifiant entièrement synthétique absolument approprié pour les conditions de course. Contient des additifs spéciaux pour offrir stabilité et un excellent comportement dans des conditions de conduite et en même temps plus longs espaces de changement d'huile.

RU:

Относится к новейшему поколению полностью синтетических масел, абсолютно соответствующих требованиям гоночных автомобилей. Содержит специальные добавки для обеспечения стабильности и великолепной отзывчивости в самых трудных условиях езды, в то же время предлагая увеличенные интервалы между заменами масла.

SR:

Poseduje formulu poslednje generacije potpuno sintetickih maziva prilagottenih trkackim uslovima. Sadrzi i posebne aditive koji omogucavaju stabilnost i izuzetno ponašanje cak i u oštroj vožnji, a pružaju i duži period zamene ulja.

RS Laboratory: 13.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece [EU] - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



TCC (Typical Chemical Characteristics)

RR 4T SAE 0W-40 / 5W-40 / 10W-60 / 10W-50

BG:
Синтетично масло от най-висок клас, абсолютно подходящо за употреба при състезателни условия. Съдържа специални добавки, които осигуряват стабилна работа на маслото при продължителни натоварвания на двигателя, като същевременно осигурява и по-дълъг интервал за смяна.

Characteristics:

Property	Method	Unit	0W-30	5W-40	10W-60	10W-50
Specific Gravity 15°C	ASTM D 1298	kg/L	0,881	0,881	0,881	0,881
Viscosity at 100°C	ASTM D 445	cSt	9,3 - 12,5	12,5 - 16,3	21,9 - 26,1	16,3 - 21,9
Viscosity Index	-	-	>145	>140	>140	>140
Pour Point	ASTM D 97	°C	<-40	<-35	<-30	<-30
Flash Point	ASTM D 92	°C	>200	>200	>200	>200
Color	-	-	Crystal gold	Crystal gold	Crystal gold	Crystal gold
Cold Cranking Simulator	ASTM D 5293	mPa-s	<6200 @ -35°C	<6600 @ -30°C	<7000 @ -25°C	<7000 @ -25°C
TBN	ASTM D 2896	mgKOH/g	7,5	7,5	7,5	7,5

Specifications:

SAE 0W-30:

API: SN/SM/SL
& JASO MA/MA 2

1L	60L
022003017	022003607

SAE 5W-40:

API: SN/SM/SL
& JASO MA/MA 2

1L	60L
022054017	022054607

SAE 10W-60:

API: SN/SM/SL
& JASO MA/MA 2

1L	60L
022106017	022106607

RS Laboratory: 13.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



TCC (Typical Chemical Characteristics)

RR 4T SAE 0W-40 / 5W-40 / 10W-60 / 10W-50

SAE 10W-50:

API: SN/SM/SL
& JASO MA/MA 2

1L	60L
022105017	022105607

Package:

12x1L Carton / 1x60L Mini-Drum



RS Laboratory: 13.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece [EU] - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.