



TCC (Typical Chemical Characteristics)

ST 4T SAE 10W-30 / 15W-50

Description:

EN:

New synthetic technology lubricant for four stroke motorbike engines. It contains high quality additives for providing perfect engine operation and maximizes the torque capacity by preventing clutch slippage.

EL:

Νέο συνθετικής τεχνολογίας λιπαντικό, ειδικά κατασκευασμένο για τετράχρονους (4T) κινητήρες μοτό υδρόψυκτους ή αερόψυκτους. Περιέχει υψηλής ποιότητας πρόσθετα, ώστε να προσφέρει τέλεια λειτουργία του κινητήρα, με μέγιστη δυνατή απόδοση χωρίς να παρουσιάζεται ολίσθηση του συμπλέκτη.

DE:

Schmiermittel der neuesten Synthetik-Technologie für Viertakt-Motorräder. Enthält Additive hoher Qualität für perfekten Leichtlauf, verhindert jedes Kupplungsrutschen und bietet so maximale Drehmomentkapazität.

FR:

Nouveau lubrifiant synthétique pour moteurs à quatre temps de motos. Il contient des additifs de haute qualité pour offrir un fonctionnement du moteur parfait et aussi pour maximiser la capacité de couple en empêchant le glissement de l'embrayage.

RU:

Новое технологичное синтетическое масло для четырехтактных двигателей мотоциклов. Содержит высококачественные добавки для обеспечения безупречной работы двигателя, а также для достижения максимального крутящего момента, предотвращая пробуксовку сцепления.

RS Laboratory: 13.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece [EU] - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



TCC (Typical Chemical Characteristics)

ST 4T SAE 10W-30 / 15W-50

Characteristics:

Property	Method	Unit	10W-30	15W-50
Specific Gravity 15°C	ASTM D 1298	kg/L	0,880	0,885
Viscosity at 100°C	ASTM D 445	cSt	9,3 - 12,5	16,3 - 21,9
Viscosity Index	-	-	>120	>120
Pour Point	ASTM D 97	°C	<-30	<-30
Flash Point	ASTM D 92	°C	>200	>210
Color	-	-	Crystal gold	Crystal gold
Cold Cranking Simulator	ASTM D 5293	mPa-s	<7000 @ -25°C	<7000 @ -20°C
TBN	ASTM D 2896	mgKOH/g	7,5	7,5

Specifications:

SAE 10W-30:

API: SN/SM/SL

& JASO MA/MA 2

1L	60L
051103017	051103607

SAE 15W-50:

API: SN/SM/SL

& JASO MA/MA 2

1L	60L
051155017	051155607

Package:

12x1L Carton / 1x60L Mini-Drum



RS Laboratory: 13.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece [EU] - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.